

Ingrained Specifications and Warranties

General:

Description: Dye Method: Fiber: Face Weight: Total Weight: Tuft Bind: Gauge: Pile Height: Total Height: Backing: Delamination: Anti-Soil and Stain Protection: Tile Size: Origin: Installation Method:

Performance:

Static Electricity: Traffic: Indoor Air Quality:

Flammability:

Radiant Panel: NBS Smoke Chamber: Methenamine Tablet:

Maintenance:

Spot Cleaning:

Professional Cleaning:

Warranties:

Lifetime Face Fiber Wear Lifetime Soil and Stain Protection Lifetime Edge Ravel Lifetime Antistatic Protection Lifetime Floor Compatibility Lifetime Floor Release Lifetime Moisture Resistance Textured loop pile carpet tile plank Injection dyed BCF Type 6,6 2-Ply Premium Nylon 15 oz. / sq. yd. 93 oz. / sq. yd. Exceeds industry standards 1/12th .13 in. .28 in. Accentuate® cushion – PVC free Exceeds industry standards Impervion® soil and stain treatment 25cm x 1m (9.85" x 39.4") U.S.A. Ashlar, staggered

< 3.5 KV (AATCC-134), Permanent Conductive Fiber Heavy commercial use Green Label Plus Certified

> 0.45 watts/cm2 (ASTM – E648, Class I)
< 450 (ASTM-E662 NFPA-258)
Self-extinguishing (DOC FF-1-70)

Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly. Hot water extraction

Lifetime Tuft Bind Lifetime Color Pattern Permanency Lifetime Cushion Resiliency Lifetime Delamination of Backing Lifetime Dimensional Stability