

## Makes Sense Specifications and Warranties

General:

Description: Textured loop pile carpet tile

Dye Method: Solution dyed

Fiber: BCF Type 6 2-Ply Premium Nylon

Face Weight: 15.5 oz. / sq. yd. Total Weight: 95.5 oz. / sq. yd.

Tuft Bind: Exceeds industry standards

Gauge: 1/12<sup>th</sup>
Pile Height: .15 in.
Total Height: .31 in.

Backing: Accentuate® cushion – PVC free Delamination: Exceeds industry standards

Anti-Soil and Stain Protection: Impervion® soil and stain treatment

Tile Size: 50cm x 50cm (19.7" x 19.7")

Origin: U.S.A. Installation Method: Ashlar

Performance:

Static Electricity: < 3.5 KV (AATCC-134), Permanent Conductive Fiber

Traffic: Heavy commercial use Indoor Air Quality: Green Label Plus Certified

Flammability:

Radiant Panel: > 0.45 watts/cm2 (ASTM – E648, Class I)

NBS Smoke Chamber: < 450 (ASTM-E662 NFPA-258)
Methenamine Tablet: Self-extinguishing (DOC FF-1-70)

Maintenance:

Spot Cleaning: Spot clean with approved carpet cleaner. Follow

manufacturer recommendations. Vacuum regularly.

Professional Cleaning: Hot water extraction

Warranties:

Lifetime Face Fiber Wear Lifetime Tuft Bind

Lifetime Soil and Stain Protection Lifetime Color Pattern Permanency

Lifetime Edge Ravel Lifetime Cushion Resiliency
Lifetime Antistatic Protection Lifetime Delamination of Backing

Lifetime Floor Compatibility
Lifetime Floor Release

Lifetime Dimensional Stability

Lifetime Moisture Resistance