



Joy Carpets & Co.

## Burnished Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	15 oz. / sq. yd.
Total Weight:	94 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.135 in.
Total Height:	.325 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Diversions Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	15 oz. / sq. yd.
Total Weight:	92 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.135 in.
Total Height:	.42 in.
Backing:	Accentuate® cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion® soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, monolithic, quarter-turn

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## High Tide Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	17.5 oz. / sq. yd.
Total Weight:	93 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.15 in.
Total Height:	.31 in.
Backing:	Accentuate® cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion® soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Ingrained Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile plank
Dye Method:	Injection dyed
Fiber:	BCF Type 6,6 2-Ply Premium Nylon
Face Weight:	15 oz. / sq. yd.
Total Weight:	93 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.13 in.
Total Height:	.28 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	25cm x 1m (9.85" x 39.4")
Origin:	U.S.A.
Installation Method:	Ashlar, staggered

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Makes Sense Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	15.5 oz. / sq. yd.
Total Weight:	95.5 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.15 in.
Total Height:	.31 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	

Specifications are subject to normal manufacturing tolerance.  
Sizes are approximate and actual carpet color may vary.



Joy Carpets & Co.

## Nexus Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	15 oz. / sq. yd.
Total Weight:	92 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.13 in.
Total Height:	.42 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Quarter-turn, ashlar, monolithic

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Oil and Water Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	15 oz. / sq. yd.
Total Weight:	94 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.14 in.
Total Height:	.32 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Outer Banks Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6,6 2-Ply Premium Nylon
Face Weight:	19 oz. / sq. yd.
Total Weight:	100 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.14 in.
Total Height:	.32 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Monolithic

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	





Joy Carpets & Co.

## Overdrive Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6,6 2-Ply Premium Nylon
Face Weight:	17 oz. / sq. yd.
Total Weight:	98 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.13 in.
Total Height:	.30 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, monolithic, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Quicken Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	15 oz. / sq. yd.
Total Weight:	92 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.13 in.
Total Height:	.42 in.
Backing:	Accentuate® cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion® soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, monolithic, quarter-turn

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Replicate Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6,6 2-Ply Premium Nylon
Face Weight:	19 oz. / sq. yd.
Total Weight:	100 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.13 in.
Total Height:	.31 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, monolithic, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Riverine Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	17.5 oz. / sq. yd.
Total Weight:	93 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.15 in.
Total Height:	.31 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Static Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	16 oz. / sq. yd.
Total Weight:	94 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.14 in.
Total Height:	.33 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Understatement Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	17.5 oz. / sq. yd.
Total Weight:	93 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.14 in.
Total Height:	.31 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	



Joy Carpets & Co.

## Up and Away Specifications and Warranties

### General:

Description:	Textured loop pile carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-Ply Premium Nylon
Face Weight:	17.5 oz. / sq. yd.
Total Weight:	93 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 <sup>th</sup>
Pile Height:	.15 in.
Total Height:	.30 in.
Backing:	Accentuate <sup>®</sup> cushion – PVC free
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion <sup>®</sup> soil and stain treatment
Tile Size:	50cm x 50cm (19.7" x 19.7")
Origin:	U.S.A.
Installation Method:	Ashlar, horizontal, vertical

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

### Flammability:

Radiant Panel:	> 0.45 watts/cm <sup>2</sup> (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

### Warranties:

Lifetime Face Fiber Wear	Lifetime Tuft Bind
Lifetime Soil and Stain Protection	Lifetime Color Pattern Permanency
Lifetime Edge Ravel	Lifetime Cushion Resiliency
Lifetime Antistatic Protection	Lifetime Delamination of Backing
Lifetime Floor Compatibility	Lifetime Dimensional Stability
Lifetime Floor Release	
Lifetime Moisture Resistance	