




## Clydesdale Cut 18 Specifications and Warranties

### General:

Description:	Cut pile broadloom
Dye Method:	<b>Digital dye injection</b>
Dye Resolution:	256 dpi
Fiber:	<b>Premium BCF Type 6 Nylon</b>
Tufted Face Weight:	18 oz / sqyd
Gauge:	1/10 <sup>th</sup>
Pile Height:	.186 in.
Primary Backing:	Woven polypropylene
Secondary Backing:	ActionBac
Secondary Backing (optional):	KangaTRAC polyurethane cushion
Anti-Soil and Stain Protection:	<b>Integrated soil and stain treatment</b>
Antimicrobial Protection:	<b>Integrated mold, mildew, and odor treatment</b>
Broadloom Width:	12'
Origin:	USA

### Performance:

Static Electricity:	< 3.5 KV (AATCC-134)
Traffic:	Commercial
Indoor Air Quality:	 <b>Green Label Plus®</b> Certifies product exceeds most stringent indoor air quality standards and are best suited for living, working, and learning environments

### Flammability:

Radiant Panel:	> 0.45 watts/cm2 (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 flaming and non-flaming (ASTM-E662 NFPA-258)

### Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow label directions
Professional Cleaning:	Vacuum regularly Hot water extraction

### Commercial Limited Warranties:

20 Year 10% Fiber Loss Abrasive Wear Warranty	- Abrasive wear of surface pile guaranteed not to exceed 10%
20 Year Texture Retention Warranty	- Guaranteed to maintain appearance under heavy foot traffic
10 Year Soil and Stains Warranty	- Provides total fiber protection against soil and stains
Lifetime Antistatic Warranty	- Built-in static control fiber
10 Year Tuft Bind Warranty	- Guaranteed to maintain superior tuft bind in high traffic areas
Fade Resistance (for indoor use only)	- Resists fading under normal indoor use

